

Think POS, Think Us!

Frontier 1370 / 1478

All in One Touch PoS



- Support P4 up to 3.06Ghz
- Unique design HeatPipe is equipped for effective cooling in high temperature environment
- Key lock is equipped to provide extra security for storage devices
- Power supply outputs 5v/12v/24v for additional peripheral devices
- AGP 8X provides high performance graphic resolution
- Possible selections of ELO or Fujitsu touch screen
- Optional Wall mount
- Frontier electronic function devices are modular design for easier maintenance
- Robust and splash-resistance, Frontier can be securely operated in any harsh environment
- Can be easily integrated with, MSR Card Reader, Smart card reader, fingerprint recognition system, Pole display and Secondary LCD display

Application:

Retail and Hospitality /
Kiosk / Casino

Peripheral:

MSR Card Reader
Pole Display
24V Power Adaptor
Removable HDD Rack
Optional 2x2.5" HDD
24X Slim type CD ROM
Slim type Combo DVD
+ CD R/W
Cash Drawer Controller
Secondary LCD Display

Compatible Operating System:

Microsoft Windows 95/98/
2000/XP/NT/
XP Embedded /WEPOS
DOS
Linux



Frontier 1370 / 1478 All in One POS System Specifications:		
Model	Frontier-1478	Frontier-1370
Touch Panel	(1) 15" ELO (5 Wires) or 15" Fujitsu (4 Wires) Resistive LCD Touch Panel with RS-232 or USB Interface (2) 15" 3M Capacitive LCD Touch Panel with RS-232 Interface	
LCD Panel	15" TFT LCD Panel with LVDS Interface	
CPU	Support Intel P-4 CPU up to 2.8 GHz / Celeron up to 2.8GHz (Socket 478 CPU)	Support Intel P3 CPU up to 1GHz / Celeron CPU up to 1.4 GHz (Socket 370 CPU)
Main Memory	184-Pin DDR RAM x 2 up to 2GB. (DDR400)	
System Chip Set	North Bridge: Intel 865GV South Bridge: Intel ICH5	North Bridge: VIA CLE266 South Bridge: VIA VT-8235
BIOS	Award BIOS	
AGP 3D Graphics Port	Intel 865GV Graphics Core, Share memory from 8MB up to 64MB	VIA CLE-266 Graphics Core, Share memory from 8MB up to 64MB
Parallel Port	1	
Serial Port	4 (1 for touch by default)	
FDD	None (USB External FDD optional)	
CD-ROM	Slim Type CD-ROM/COMBO/DVD	
HDD	3.5" IDE HDD	
USB and Powered USB Port	6 * USB port (USB 2.0) * Two USB port (Ver. 2.0, Front) * Two Powered USB port (Ver. 2.0, 1x 12V / 1x 24V , Rear) * Two USB Port (Ver.2.0) on M/B for option.	
Thermal Solution	Heatpipe	Heatsink
Internal Power Supply	250W Flex ATX Industrial PSU.	
AC Power Source	AC 90 to 264V Full Range.	
Ethernet Port	10/100 Base-T	10/100 Base-T
Audio Port	Line In/ Line Out / MIC In.	
Keyboard Port	Yes	
Mouse Port	Yes	
System Size	215MM(L) x 380MM(W) x 600MM(H)	
Operation Temperature	0°C to 40°C (without HDD up to 50°C)	

datavan
Think POS, Think Us



10F., NO186, Jian 1st Rd., Jhonghe City, Taipei County 235. Taiwan (R.O.C.)
TEL: 886-2-8227-2556 FAX: 886-2-8227-2330 <http://www.datavan.com.tw>

