

10.4" Customer Display



Models: OT10SA (VGA Input) / OT10SC (USB Input)

- Optimal display size as 211.2 x 158.4.
- Low power consumption 8W(VGA)or 2.5W(USB)LED backlight.
- Light weight only 1.00kg.
- Optional wall mount bracket.
- Optional metal base for desktop use.

Model No.	OT10SA	OT10SC
Cabinet Color	Black	
Display Area	211.2 * 158.4 mm	
Optimal Resolution	800 * 600	
Panel Brightness	300 cd/m ² (typ)	180 cd/m ² (typ)
Contrast Ratio	500:1(typ)	
Response Time	30 ms (typ)	
LCD Viewing Angle(L/R/U/D)	75 / 75 / 50 / 60	
Input Video signal connector	D-Sub 15 pins	USB B type
Power consumption	8W	2.5W
Input Frequency	Horizontal: 31.5-60.2 kHz Vertical : 56.3Hz-75Hz	
Power supply	DC 12V +/- 10%	DC 5V +/- 10%
Tempurature	Operating : 0°C~40°C Storage : -10°C~50°C	
Humidity	Operating : 20%~80% Storage : 10%~90%	
Weight	840 g (Net)	
Physical Dimension	239.6 (W) * 191.6 (H) * 36.3 (D) mm	
Approvals	CE, FCC, BSMI	
Wall Mount Type	VESA 75 * 75 mm	
Optional item		
Cabinet Color	White	
Touch Screen	5W Resistive Taiwan touch (Model: OT10TA)	NA
Stand Base	Metal base (Model: OT10TA)	NA
Wall Mounting	Bracket	