

OTEKsys 12" Ecological POS Monitor



Features



1. Spill and Dust proof design in front bezel, meets IP54 requirement ideally for retail and hospitality environment



2. Sturdy and Robust base



3. Two colors logo printing



4. Screen tilting angle freely up to 90 degree vertically



5. Integrate Elo Or Taiwan local brand 5 Wires Resistive touch

6. Optional detachable MSR for stock flexibility



7. Optional choices of 2nd display for advertisement application



8. Reuse packing box as storage cabinet (Patent under applying)

Specification

Model	OT12N Series
Cabinet Color	Black or White
Display Size	12.1"
Active Area	246 * 184.5 mm
Optimal Resolution	800 * 600
Brightness	370 nits (typ)
Contrast Ratio	450 : 1
Response Time	45 ms (typ)
Viewing Angle(L/R/U/D)	70 / 70 / 50 / 60 (typ)
Input Video Connector	D-Sub 15 pins
Power Consumption	20W
Input Frequency	Horizontal : 31.5-60.2 kHz Vertical : 56.3Hz~75 Hz
Power Supply	DC 12V +/- 10%
Temperature	Operating : 0 °C~40°C Storage : -10°C~50°C
Weight (net)	4.67 kgs
Physical Dimension	315(W) * 317 (H) * 200 (D) mm
Approvals	CE / FCC / CCC / BSMI
Wall Mount type	VESA 75 * 75
Warranty	3 years
Optional Items	
Touch Technology	5W Resistive Elo or Taiwan brand
Color	Black or White
Wall Mount	Bracket
MSR	3 Tracks
2nd Display	OT07S / OT08S / OT84S / OT84T OT10S

Product specifications subject to change without prior notice

Made in Taiwan ROC

Dimensions

